

MATERIAL SAFETY DATA SHEET

I. IDENTIFICATION

Product Name: SILK SHEEN
Chemical Name: Hydrocarbon Distillates
Cas Number: MIXTURE
Information Telephone Number: (480) 951-0003

II. COMPONENTS AND HAZARD INFORMATION

<u>Component</u>	<u>CAS NO. of Component</u>	<u>TLV of Component</u>	<u>OSHA TWA</u>	<u>Approximate Concentration</u>
Mineral Spirits	64741-65-7	Not Established	N.E.	>90.0%
Mineral Oil	8042-47-5	Not Established	5 mg/m ³	5.00%

DOT Hazard Classification: Combustible Liquid NOS (contains Petroleum Distillates), NA 1993, PG III
Hazardous Materials Identification System (HMIS)

Health	Flammability	Reactivity	BASIS
1	2	0	Recommended by Laidlaw
TLV for Total Product			BASIS
N/A			Calculated TLV REF ACGIH

III. PHYSICAL DATA

Boiling Point	<u>340° F</u>	Vapor Density	<u>> 1.0 (Air=1.0)</u>
Vapor Pressure	<u>Not Determined</u>	Percent Volatiles	<u>95.00%</u>
Specific Gravity	<u>0.772</u>	Evaporation Rate	<u>Not Determined</u>

IV. FIRE AND EXPLOSION DATA

Flash Point (°F TCC) 145° F
Extinguishing Media Regular foam or dry chemical.

Special Firefighting Procedure Self contained breathing air apparatus operated in positive pressure mode.

Unusual Fire & Explosion Hazards Vapors may travel along floor and be ignited by energy source distant from the handling point.

National Fire Protection Association (NFPA -) Hazard Identification

Health	Flammability	Reactivity	BASIS
1	2	0	Recommended by Laidlaw

V. HEALTH HAZARD DATA

Effects of Overexposure:

Eyes: Can cause severe irritation, redness, tearing, blurred vision.

Skin: Prolonged or repeated contact may cause moderate irritation.

Breathing: Excessive inhalation of vapors may cause nasal and respiratory irritation.

Swallowing: Can cause gastrointestinal irritation, vomiting, nausea, and diarrhea. Aspiration on material into lungs can be fatal.

